

## SAFETY MEETING QUIZ

Name:

Date:

Safety Topic: V1-28B Personal Protection – Foot Protection

1. OSHA requires that adequate foot protection be used whenever the work conditions pose hazards that could cause a foot injury.
  - a. True
  - b. False
2. When determining footwear requirements, many factors should be considered during the hazard assessment process, including
  - a. the tasks being performed.
  - b. environmental conditions.
  - c. electrical hazards.
  - d. all of the above.
3. A \_\_\_\_\_-resistant sole may be required when a working environment may potentially have sharp objects like nails or broken glass.
  - a. water
  - b. puncture
  - c. heat
  - d. chemical
4. A \_\_\_\_\_ guard may be required when additional protection is needed for the top of the foot.
  - a. metatarsal
  - b. insulated
  - c. ESD
  - d. waterproof
5. Shoes and boots should be replaced when the tread pattern is gone from the rear two-thirds of the heel.
  - a. True
  - b. False



# SAFETY MEETING QUIZ

## ANSWER KEY

**Safety Topic:** V1-28B Personal Protection – Foot Protection

1. OSHA requires that adequate foot protection be used whenever the work conditions pose hazards that could cause a foot injury.  
  - ☒ a. True
  - b. False
  
2. When determining footwear requirements, many factors should be considered during the hazard assessment process, including  
  - a. the tasks being performed.
  - b. environmental conditions.
  - c. electrical hazards.
  - ☒ d. all of the above.
  
3. A \_\_\_\_\_-resistant sole may be required when a working environment may potentially have sharp objects like nails or broken glass.  
  - a. water
  - ☒ b. puncture
  - c. heat
  - d. chemical
  
4. A \_\_\_\_\_ guard may be required when additional protection is needed for the top of the foot.  
  - ☒ a. metatarsal
  - b. insulated
  - c. ESD
  - d. waterproof
  
5. Shoes and boots should be replaced when the tread pattern is gone from the rear two-thirds of the heel.  
  - ☒ a. True
  - b. False

