

# SAFETY MEETING QUIZ

Name:

Date:

Safety Topic: V1-06B Man Lifts – Aerial Lifts

1. Before operating any aerial lift, there are two inspections that need to happen:
  - a. hidden health hazards inspection and electrical safety inspection.
  - b. tool belt size inspection and hand tool inspection.
  - c. pre-start inspection of the vehicle and the lift and the work zone inspection.
  - d. OSHA focus four hazard inspection and ergonomic safety inspection.
2. If any part of the aerial lift is not working properly,
  - a. remove the lift from service and tag out until repairs are made.
  - b. let a supervisor know after the job is completed.
  - c. the lift operator can decide if they think it's safe enough or not.
  - d. make a note in the maintenance record, but continue the job for the day.
3. The outriggers should be set on a \_\_\_\_\_ surface.
  - a. sloped
  - b. solid, level
  - c. softer
  - d. slippery
4. Never move an aerial lift truck when the boom is elevated in a working position with workers in the basket unless the equipment is specifically designed for that type of operation.
  - a. True
  - b. False
5. To calculate the load on the platform, don't forget to add the weight of
  - a. all workers.
  - b. all tools.
  - c. all materials.
  - d. all of the above.



# SAFETY MEETING QUIZ

## ANSWER KEY

**Safety Topic:** V1-06B Man Lifts – Aerial Lifts

1. Before operating any aerial lift, there are two inspections that need to happen:
  - a. hidden health hazards inspection and electrical safety inspection.
  - b. tool belt size inspection and hand tool inspection.
  - ☒ c. pre-start inspection of the vehicle and the lift and the work zone inspection.
  - d. OSHA focus four hazard inspection and ergonomic safety inspection.
  
2. If any part of the aerial lift is not working properly,
  - ☒ a. remove the lift from service and tag out until repairs are made.
  - b. let a supervisor know after the job is completed.
  - c. the lift operator can decide if they think it's safe enough or not.
  - d. make a note in the maintenance record, but continue the job for the day.
  
3. The outriggers should be set on a \_\_\_\_\_ surface.
  - a. sloped
  - ☒ b. solid, level
  - c. softer
  - d. slippery
  
4. Never move an aerial lift truck when the boom is elevated in a working position with workers in the basket unless the equipment is specifically designed for that type of operation.
  - ☒ a. True
  - b. False
  
5. To calculate the load on the platform, don't forget to add the weight of
  - a. all workers.
  - b. all tools.
  - c. all materials.
  - ☒ d. all of the above.

