

# SAFETY MEETING QUIZ

Name:

Date:

Safety Topic: *V1-41B Personal Protection – Hand Protection*

1. If a workplace hazard assessment reveals that employees face potential injury to their hands that cannot be eliminated through engineering and work practice controls, workers must wear appropriate hand protection.
  - a. True
  - b. False
  
2. If workers don't wear gloves as required, they may be at risk for
  - a. slips, trips, and falls.
  - b. hearing damage.
  - c. cuts, lacerations, abrasions, or puncture wounds.
  - d. respiratory distress.
  
3. Gloves should fit
  - a. loose.
  - b. snug.
  - c. stiff.
  - d. tight.
  
4. A factor that may influence the selection of protective gloves may be
  - a. size and comfort.
  - b. grip requirements.
  - c. thermal protection.
  - d. any of the above.
  
5. Gloves contaminated with flammable or combustible materials should not be used while working near
  - a. water.
  - b. other workers.
  - c. fire extinguishers.
  - d. an ignition source.



# SAFETY MEETING QUIZ

## ANSWER KEY

**Safety Topic:** V1-41B Personal Protection – Hand Protection

1. If a workplace hazard assessment reveals that employees face potential injury to their hands that cannot be eliminated through engineering and work practice controls, workers must wear appropriate hand protection.
  - a. True
  - b. False
  
2. If workers don't wear gloves as required, they may be at risk for
  - a. slips, trips, and falls.
  - b. hearing damage.
  - c. cuts, lacerations, abrasions, or puncture wounds.
  - d. respiratory distress.
  
3. Gloves should fit
  - a. loose.
  - b. snug.
  - c. stiff.
  - d. tight.
  
4. A factor that may influence the selection of protective gloves may be
  - a. size and comfort.
  - b. grip requirements.
  - c. thermal protection.
  - d. any of the above.
  
5. Gloves contaminated with flammable or combustible materials should not be used while working near
  - a. water.
  - b. other workers.
  - c. fire extinguishers.
  - d. an ignition source.

